


RUSTLER



PRE-ORDER



Rustler MIG PRO PULSE compact welding inverters are your solution of choice for the most common welding challenges. Equipped with the latest inverter technology and pulse function, they combine low energy consumption with optimized welding performance.



To place your orders: Please contact your local ESAB Sales Representative

RUSTLER



SPECIFICATIONS

Model	Rustler EM 350 PRO Pulse	Rustler EM 350Cw PRO Pulse	Rustler EM 350Cw MV PRO Pulse
Mains Voltage	400 V $\pm$ 15%, 3 Φ , 50/60 Hz	400 V $\pm$ 15%, 3 Φ , 50/60 Hz	400 V $\pm$ 15%, 3 Φ , 50/60 Hz 230 V $\pm$ 15%, 3 Φ , 50/60 Hz
Primary Current I MAX	20.6 A	20 A	40 A (230 VAC) 20 A (400 VAC)
Primary Current I eff	13 A	13 A	25.3A (230 VAC) 13A (400 VAC)
Idle Power	< 30 W	< 40 W	< 40 W
Mains Cable	4x2,5mm ² , 4m	4x2,5mm ² , 4m	4x2,5mm ² , 4m
Supply Plug	CEE16	CEE16	CEE32
Rated kVA	14.0 kVA	14.0 kVA	14.0 kVA
Recommended Generator		17 kW	17 kW
MIG/MAG Welding Output 40% Duty Cycle	350 A/31.5 V	350 A/31.5 V	350 A/31.5 V
Current Range, MIG/MAG	30-350 A	30-350 A	30-350 A
Voltage Range, MIG/MAG	15.5-31.5 V	15.5-31.5 V	15.5-31.5 V
Open Circuit Voltage, MIG/MAG	71.0 VDC	71.0 VDC	74.0 VDC
MMA Welding Output 40% Duty Cycle	320 A/32.8 V	320 A/32.8 V	320 A/32.8 V
Current Range, MMA	20-320 A	20-320 A	20-320 A
Voltage Range, MMA	20.8-32.8 V	20.8-32.8 V	20.8-32.8 V
Open Circuit Voltage, MMA	66.6 VDC	66.6 VDC	74.0 VDC
Power Factor at Max Current	0.9	0.8	0.8
Efficiency at Max Current	89%	85%	85%
Wire Feed Speed Range	1.5 – 22 m/min		
Wire Spool Size	200 mm and 300 mm		
Approvals	CE / UKCA		
Enclosure Class	IP23		
Operating Temperature	-10 to +40 °C		
Power Source Dimensions	977x487x800	977x487x1230	977x487x1230
Power Source Weight	61 kg	80 kg	83 kg

Delivery includes: Power source with 4 m input cable 3 Ph 16A/32A plug, 3 m work lead, gas hose with quick connector 4 m, drive rolls for 0.9/1.0 and 1.2mm wire.

Package: 350C/350C Synergic/350C MV Pulse includes Exeor PSF 315 torch with R4, 4 m, 350Cw Synergic includes Exeor PSF 420w torch with R4, 4 m.

ORDERING INFORMATION

Power source	Item no.	List price, currency	Discount	Net	Machine Options	Quantity
Rustler EM 350C PRO Pulse	0448350885				Power source + Toolbox + Torch	
	0448350995				Power source	
Rustler EM 350Cw PRO Pulse	0448350886				Power source + Toolbox + Torch	
	0448350996				Power source	
Rustler EM 350Cw MV PRO Pulse	0448350887				Power source + Toolbox + Torch	
	0448350997				Power source	